

PERFORMANCE TOP RATED EFFICIENCY



WWW.GULFSTREAMHEATPUMP.COM









#### PERFORMANCE AND EFFICIENCY:

#### **INTELLIGENT CONTROL:**

(Additional wiring may be required)

#### **4-Sided Evaporator Coil**

Super-sized for maximum efficiency Higher Performance in all weather Engineered for a smaller footprint

## GPS Affordable Spa Automation

Isolates the spa, energizes the pump & switches thermostats Plug-ins for 2 actuators Wireless options available

#### 2" Full Flow Titanium Heat Exchanger

Pipe size does not reduce once inside the unit Maximum water flow design for higher efficiency Lifetime titanium warranty against corrosion

#### **Solarwize Solar Heating Controller**

Solar pool automation for hybrid pool heating control Prioritizes solar pool heating for maximum efficiency Actuator Plug-in & roof sensor connections

#### **Ultra-Quiet Design**

Quiet scroll compressor Commercial grade fan motor designed for quiet operation Only 56db while in operation

#### **Compatible with all external Automation**

Simple connection and programming Seamless integration with all major brands of automation

#### **Ultimate Warranty**

**Industry Best 5: Years Labor 10 Years Parts** 

#### **Even Heat**

Maintains the perfect temperature 24-hours a day

# **ADVANCED ASSEMBLY AND TESTING**

#### **Helium Leak Testing**

100-times more accurate than the competition Ensures optimized performance in every unit

### **Mass Flow Charging**

The most accurate way to ensure proper refrigerant charging Computerized accuracy to 1/100th of an ounce

#### **Rust Proof ABS Cabinet**

Strong ABS cabinet designed for harsh climates UV inhibitors added for lifetime durability Avoid the metal-cabinet regret

#### **Comprehensive Final Run Test**

Computerized quality control testing cannot be bypassed Every-component in every-unit tested every-time A "Perfect" unit every time for the ultimate peace of mind

UNIT SPEC	HI-110	HI-125	HI-150
BTU/COP AHRI HIGH TEST POINT(80/80/80) LOW TEST POINT (50/63/80)	<b>110,000/6.2</b> 66,000/4.1	<b>117,000/6.3</b> 74,000/4.1	136,000/6.0 85,000/4.0
MIN AMPS / MAX BREAKER	37/40	37/50	37/50
WEIGHT (SHIPPING)	215 LBS (243 LBS)	237 LBS (265 LBS)	239 LBS (267 LBS)
DIMENSIONS (SHIPPING)	31 X 31 X 38 (33 X 31 X 43)	31 X 31 X 42 (33 X 31 X 47)	31 X 31 X 42 (33 X 31 X 47)







