



SPECIFICATIONS AND PERFORMANCE DATA

FOR ALL GULFSTREAM HI-E SERIES HEAT PUMPS

HEAT EXCHANGER:	100%Titanium Heat Exchanger	COMPRESSOR:	SCROLL
MIN /MAX FLOW:	20/70 GALLONS	PLUMBING SIZE:	2"
RECOMMENDED FLOW:	45 GALLONS	ADDITIONAL SPECS:	SEE INDIVIDUAL UNITS

HI 5-R-A
THE HIGH-5

ORIGINAL TEST POINT	80/80/80 BTU: 110,000 ◇ COP: 6.4
Outside AHRI Test Standard	
AHRI Testing →	[80/63/80 BTU: 99,000 ◇ COP: 6.0 50/63/80 BTU: 66,000 ◇ COP: 4.1
MinAmps/MaxBreaker	37/40
Dimensions (Shipping)	31" x 31" x38" (33"x 31" x 43")
Weight (Shipping)	218 lbs (253 lbs)

5 YEARS PARTS & LABOR WARRANTY *
LIFETIME ON TITANIUM HEAT EXCHANGER

5 YEARS PARTS & 2 YEARS LABOR WARRANTY + LIFETIME ON TITANIUM HEAT EXCHANGER *

HE 90-R-A	AHRI CERTIFIED TEST RESULTS
80/80/80: BTU: 90,000 ◇ COP: 6.3	80/63/80: BTU: 84,000 ◇ COP: 5.8
OUTSIDE ARI STANDARD	50/63/80: BTU: 56,000 ◇ COP: 4.0
MIN AMPS /MAX BREAKER: 36/40	DIMENSIONS" (SHIPPING): 31 x 31 x 34 (33 X 31 X 39)
WEIGHT (SHIPPING): 210 LBS/245 LBS	

HE 110-R-A	AHRI CERTIFIED TEST RESULTS
80/80/80: BTU: 110,000 ◇ COP: 6.4	80/63/80: BTU: 99,000 ◇ COP: 6.0
OUTSIDE ARI STANDARD	50/63/80: BTU: 66,000 ◇ COP: 4.1
MIN AMPS /MAX BREAKER: 37/40	DIMENSIONS" (SHIPPING): 31 x 31 x 38 (33 X 31 X 43)
WEIGHT (SHIPPING): 218 LBS/253 LBS	

HE 125-R-A Available in 3-Phase and Heat & Cool	AHRI CERTIFIED TEST RESULTS
80/80/80: BTU: 120,000 ◇ COP: 6.3	80/63/80: BTU: 109,000 ◇ COP: 5.9
OUTSIDE ARI STANDARD	50/63/80: BTU: 74,000 ◇ COP: 4.1
MIN AMPS /MAX BREAKER: 37/50	DIMENSIONS" (SHIPPING): 31 x 31 x 38 (33 X 31 X 43)
WEIGHT (SHIPPING): 218 LBS/253 LBS	

HE 150-R-A Available in 3-Phase	AHRI CERTIFIED TEST RESULTS
80/80/80: BTU: 136,000 ◇ COP: 6.0	80/63/80: BTU: 124,000 ◇ COP: 5.4
OUTSIDE ARI STANDARD	50/63/80: BTU: 85,000 ◇ COP: 4.0
MIN AMPS /MAX BREAKER: 37/50	DIMENSIONS" (SHIPPING): 32 x 32 x 40 (34 X 32 X 45)
WEIGHT (SHIPPING): 222 LBS/257 LBS	

5 YEARS PARTS & 2 YEARS LABOR WARRANTY + LIFETIME ON TITANIUM HEAT EXCHANGER *

* See Written Warranty For Complete Details